

## **Integrated Marketing Group 1800AMA**

. . . . . . . . . . . . .

Integrated Marketing Group style 1800AMA is a **specialized satin weave**, featuring a unique vacuum metalized polyester film. This industry-strength film offers **powerful heat protection while still maintaining its high quality**; 1800AMA is also **water-resistant** and **abrasion-resistant**, making it an ideal choice for a wide range of applications, including heat shields, expansion joints, valve and pipe covers, engine compartment linings, die cut gaskets, and fire resistant articles.

Values	
Weight	20 oz./sy (678.1 g/sm) +/- 10%
Thickness	0.031 inches (.7874 mm) +/- 10%
Roll Length	50 yards (45.7 m)
Tensile Strength	Warp: 250 lbs./inch (44.6 kg/cm) Fill: 250 lbs./inch (44.6 kg/cm)
Tear Strength	Warp: 50 lbs. (22.7 kg) Fill: 50 lbs. (22.7 kg)
Burst Strength	550 psi (38.7 kg/scm)
Flame Resistance	Char length: 1" max Afterflow: 1 sec. max Flame out: 1 sec. max
Temperature Resistance	Aluminum: 600° F (315.6° C) Silica: 1800° F (982.2° C)

1740 W. Katella Ave. Suite A, Orange, CA 92867 Phone: 714-771-2401 Fax: 714-771-3925