

Integrated Marketing Group 20000S

Integrated Marketing Group style 20000S is a **specialized fiberglass fabric** made with a unique satin weave. This fabric is of the highest grade, featuring a **special orange/red silicone coating** that can resist the high temperatures your industry demands. This one-of-a-kind coating is also **water and oil resistant**, **flame retardant and chemical resistant**. This strong fabric works well for all sorts of wide-ranging uses, including welding curtains, expansion joints, equipment covers, flange covers and removable insulation pads. APPROVED

Values

| Weight | 20 oz/sy (678.1 g/sm) +/- 10% |
|------------------------|---|
| Thickness | 0.015 inches (.381 mm) +/- 10% |
| Tensile Strength | Warp: 300 lbs./inch (53.6 kg/cm) Fill: 225 lbs./inch (40.2 kg/cm) |
| Tear Strength | Warp: 50 lbs. (22.7 kg) Fill: 50 lbs. (22.7 kg) |
| Burst Strength | 600 psi (42.2 kg/scm) |
| Flame Resistance | Char Length: 1/16 inch max |
| Temperature Resistance | Cold -67°F (-55°C) Continuous 500°F (260°C) Base Fabric 1000°F (537.8°C) Continuous |

1740 W. Katella Ave. Suite A, Orange, CA 92867 Phone: 714-771-2401 Fax: 714-771-3925