




Integrated Marketing Group

Integrated Marketing Group 1700SS

Integrated Marketing Group style 1700SS is a **specialized fiberglass fabric** made with satin weave. The dynamic fabric features a **unique silver silicone coating** able to resist high temperatures. This high-quality coating is **flame retardant**, and provides **excellent resistance to water, chemicals and oil**. Major applications for 1700SS range across industries: from welding curtains to expansion joints, from equipment and flange covers to removable insulation pads, you can trust this tough, heavy-duty fabric to fit your specific needs.  **APPROVED**

Values

Weight	ASTM-D-3776-96 17 oz/sy (576.4 g/sm) +/- 10%
Thickness	ASTM-D-1777-96 0.015 inches (.381 mm) +/- 10%
Tensile Strength	ASTM-D-5034-95 Warp: 300 lbs./inch (53.6 kg/cm) Fill: 225 lbs./inch (40.2 kg/cm)
Tear Strength	ASTM-D-5587-96 Warp: 50 lbs. (22.7 kg) Fill: 50 lbs. (22.7 kg)
Burst Strength	ASTM-D-3786-87 600 psi (42.2 kg/scm)
Flame Resistance	FED 191/5903.2 Char Length: 1/16 inch max (.16 cm)
Temperature Resistance	FED SPEC HHB-100B Cold -67°F (-55°C) Continuous 500°F (260°C) Base Fabric 1000°F (537.8°C) Continuous

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.