




Integrated Marketing Group

Integrated Marketing Group 2000SS

Integrated Marketing Group style 2000SS is a **specialized fiberglass fabric** made with a unique satin weave. This fabric is of the highest grade, featuring a **special silver silicone coating** that can resist the high temperatures your industry demands. This one-of-a-kind coating is also **water and oil resistant, flame retardant and chemical resistant**. This strong fabric works well for all sorts of wide-ranging uses, including welding curtains, expansion joints, equipment covers, flange covers and removable insulation pads.  **APPROVED**

Values

Weight	20 oz/sy (678.1 g/sm) +/- 10%
Thickness	0.015 inches (.381 mm) +/- 10%
Tensile Strength	Warp: 300 lbs./inch (53.6 kg/cm) Fill: 225 lbs./inch (40.2 kg/cm)
Tear Strength	Warp: 50 lbs. (22.7 kg) Fill: 50 lbs. (22.7 kg)
Burst Strength	600 psi (42.2 kg/scm)
Flame Resistance	Char Length: 1/16 inch max
Temperature Resistance	Cold -67°F (-55°C) Continuous 500°F (260°C) Base Fabric 1000°F (537.8°C) Continuous

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.