



## Integrated Marketing Group

---

### **Integrated Marketing Group 138AMA-RDUCS**

Integrated Marketing Group style 138AMA-RDUCS is a **specialized lightweight fiberglass fabric**, designed specifically for **industry-strength thermal protection**. Laminated with a **high-quality polyester film**, this unique fabric is vacuum metallized to offer **industry-standard heat and light reflectivity**. In addition, 138AMA-RDUCS is laminated with uncured red silicone rubber, making it highly flexible and **able to conform to even the most complex components and intricate shapes**. With such unique features, this surface excels as a fabric for thermal barriers and other thermal-protective usage.

---

### **Values**

Weight	12 oz/sy (406.9 g/sm) +/- 10%
Thickness	0.012 inches (.3048 mm) +/- 10%
Tensile Strength	Warp: 225 lbs./inch (40.2 kg/cm) Fill: 200 lbs./inch (35.7 kg/cm)
Flame Resistance	Char length: < 1 inch Afterglow: < 2 seconds Flame out: < 2 seconds
Temperature Resistance	500°F (260°C) operating temperature

---

1740 W. Katella Ave. Suite A, Orange, CA 92867  
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.