



Integrated Marketing Group

Integrated Marketing Group 2025 2% Acrylic

Integrated Marketing Group style 2025 with 2% Acrylic Coating is a **specialized plain weave fiberglass fabric**, featuring **a light coating of acrylic specifically designed for fabric stabilization and raveling reduction**. 2025 is uniquely designed for a wide range of fabric applications, including insulation lagging or jacketing and removable insulation pads. 2025 stands out as a powerful fabric, featuring a design that allows it to **withstand high heat while still maintaining superb fabric strength**. 2025 also meets **MIL-C-20079H, Type I, Class 9**.

Values

Weight	18.0 oz/sy (271.2 g/sm) (610.3 g/sm) +/- 10%
Thickness	0.028 inches (.7112 mm) +/- 10%
Tensile Strength	Warp: 300 lbs./inch (53.6 kg/cm) (53.6 kg/cm) Fill: 150 lbs./inch (26.8 kg/cm) (28.8 kg/cm)
Count	Warp: 20 ends/inch Fill: 14 ends/inch
Temperature Resistance	To 1000°F (540°C)

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.