



## Integrated Marketing Group

### Integrated Marketing Group 2523RA

Integrated Marketing Group style 2523RA is a **unique plain weave fiberglass product**, featuring a specialized red acrylic coating. This potent coating is **fire-retardant**, and the powerful fabric is **incombustible**, making 2523RA a superb choice for welding curtain material. 2523RA also provides **high visibility for safety and resistance to sparks, abrasion, water and most chemicals**, to ensure the utmost safety of your employees. Major applications for this product include vertical welding curtains for spark and spray containment, arc flash barriers and fire retardant weather barrier material and grinding shields. **FM APPROVED**

### Values

Weight	16.5 oz/sy (559.4 g/sm) +/- 10%
Thickness	0.016 inches (.4064 mm) +/- 10%
Tensile Strength	Warp: 300 lbs./inch (53.6 kg/cm) Fill: 270 lbs./inch (48.2 kg/cm)
Tear Strength	Warp: 35 lbs. (15.9 kg) Fill: 30 lbs. (13.6 kg)
Burst Strength	475 psi (33.4 kg/scm)
Flame Resistance	Char Length: 1 inch max. Afterglow: 1 sec. max. Flame Out: 0 sec. max
Temperature Resistance	0°F (-17.8°C) to 300°F (148.9°C)

1740 W. Katella Ave. Suite A, Orange, CA 92867  
 Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.