




## Integrated Marketing Group

### Integrated Marketing Group 3200SS

Integrated Marketing Group style 3200SS is a **specialized fiberglass fabric**, made with a satin weave. 3200SS features a **unique silver silicone coating**, specifically designed to resist high temperatures. The powerful silicone coating is also **water-resistant, oil-resistant, and chemical-resistant**, in addition to being **flame retardant**. 3200SS is an optimal fabric for a variety of applications, including welding curtains, expansion joints, equipment covers, flange covers and removable insulation pads.  **APPROVED**

### Values

Weight	32 oz/sy (1085.0 g/sm) +/- 10%
Thickness	0.037 inches (.9398 mm) +/- .001
Tensile Strength	Warp: 400 lbs./inch (71.4 kg/cm) (28.1 kg/scm) Fill: 350 lbs./inch (62.5 kg/cm)
Tear Strength	Warp: 65 lbs. (29.5 kg) Fill: 55 lbs. (25.0 kg)
Burst Strength	750 psi (52.7 kg/scm)
Flame Resistance	Char length: 1 inch Flame out: 1 second
Temperature Resistance	Cold -67°F (-55°C) Continuous 100hrs at 500°F (260°C), no change Base Fabric 1000°F (537.8°C) Continuous

1740 W. Katella Ave. Suite A, Orange, CA 92867  
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.