



Integrated Marketing Group

Integrated Marketing Group 140, 160, 180 Fiberglass Tape

Integrated Marketing Group fiberglass tape is a 100% fiberglass woven tape and will **withstand temperatures of up to 1000 °F**. This tape is available in **white or heat cleaned**. It is also available as **drop warp (bolt hole)**. This product is ideal for gasketing, heat shielding, pipe wrap, and personnel protection.

Values

Plain

Drop Warp

	1/16"	1/8"	1/4"	1/16"	1/8"	1/4"
Thickness (±10%)	.063" (1.5 mm)	.125" (3 mm)	.25" (6 mm)	.063" (1.5 mm)	.125" (3 mm)	.25" (6 mm)
Breaking Strength Warp	400 lbs./inch (2100 Newtons/5 cm)	400 lbs./inch (2100 Newtons/5 cm)	400 lbs./inch (2100 Newtons/5 cm)	400 lbs./inch (2100 Newtons/5 cm)	400 lbs./inch (2100 Newtons/5 cm)	400 lbs./inch (2100 Newtons/5 cm)
Breaking Strength Fill	300 lbs./inch (2626 Newtons/5 cm)	300 lbs./inch (2626 Newtons/5 cm)	300 lbs./inch (2626 Newtons/5 cm)	300 lbs./inch (2626 Newtons/5 cm)	300 lbs./inch (2626 Newtons/5 cm)	300 lbs./inch (2626 Newtons/5 cm)
Temperature Resistance Continuous	1000°F (550°C)	1000°F (550°C)	1000°F (550°C)	1000°F (550°C)	1000°F (550°C)	1000°F (550°C)
Width	1" - 4"	1" - 4"	1" - 4"	1" - 4"	1" - 4"	1" - 4"

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.