



Integrated Marketing Group

Integrated Marketing Group 1500SS

Integrated Marketing Group style 1500SS is a **specialized fiberglass fabric** made with a unique satin weave. The dynamic fabric features a **unique silver silicone coating** able to resist high temperatures. This high-quality coating is **flame retardant**, and provides **excellent resistance to water, chemicals and oil**. Major applications for 1500SS range across industries: from welding curtains to expansion joints, from equipment and flange covers to removable insulation pads, you can trust this tough, heavy-duty fabric to fit your specific needs.  **APPROVED**

Values

Weight	15 oz/sy (508.6 g/sm) +/- 10%
Thickness	0.014 inches (.356 mm) +/- 10%
Tensile Strength	Warp: 300 lbs./inch (53.6 kg/cm) Fill: 225 lbs./inch (40.2 kg/cm)
Tear Strength	Warp: 50 lbs. (22.7 kg) Fill: 50 lbs. (22.7 kg)
Burst Strength	600 psi (42.2 kg/scm)
Flame Resistance	Char Length: 1/16 inch max
Temperature Resistance	Cold -67°F (-55°C) Continuous 500°F (260°C) Base Fabric 1000°F (537.8°C) Continuous

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.